



NOTES

- (1) RESISTANCES IN OHMS, K=1000, MEG=1000000.
- (2) RESISTORS ±5% 1/2 WATT UNLESS OTHERWISE SPECIFIED.
- (3) CAPACITANCES IN UUF UNLESS OTHERWISE SPECIFIED.
- (4) CAPACITORS ±20% 500WVDC UNLESS OTHERWISE SPECIFIED.
- (5) *C110 AND C117 MATCHED TO 5%.
- (6) UPPER WAVEFORM 20 CYCLES. LOWER WAVEFORM 20 KILOCYCLES.
- (7) WAVEFORMS TAKEN WITH SWITCHES IN MAXIMUM CLOCKWISE POSITION. FOR FURTHER INFORMATION SEE SECTION VI.
- (8) S101-INPUT NETWORK-2 POLES, 5 POSITIONS.
- (9) S102-INPUT SENSITIVITY-3 POLES, 2 POSITIONS.
- (10) S103-MATCHED LOAD IMPEDANCE-9 POLES, 5 POSITIONS.
- (11) ALL SWITCHES SHOWN IN MAXIMUM CLOCKWISE POSITION, LOOKING FROM THE FRONT.

MODEL UF-101A		
REVISED 1-11-60	FIGURE-10	DRAWN BY AHW
DATE 4-17-59		APPROVED BY [Signature]
ULTRA LOW DISTORTION POWER AMPLIFIER		
KROHN-HITE CORPORATION CAMBRIDGE, MASSACHUSETTS		DRAWING NUMBER UF-101A